

## **Features**

- Scalable expansion up to 16 pcs in parallel.
- Flexible Installation: Floor-Mounted.
- LiFePO4: Higher safe performance and longer cycle life.
- Multiple Protection with built-in smart BMS, and fuse.
- Compatible with leading inverter brands.
- Up to 5-year long warranty.







FLA12300

Guangzhou Felicity Solar Technology Co.,Ltd.











Model	FLA12100	FLA12200	FLA12300
Battery Type	LiFePO4		
Nominal Energy	1.28kWh	2.56kWh	3.75kWh
Nominal Voltage	12.8V	12.8V	12.8V
Operating Voltage	11.2V-14.4V	11.2V-14.4V	11.2V-14.4V
Recommend Charge/Discharge Current[1]	≤100A	≤100A	≤100A
Recommend Charge/Discharge Power[1]	≤1,250W	≤1,500W	≤1,875W
Maximum Charge/Discharge Current(15s)	150A	200A	200A
Maximum Charge/Discharge Power(15s)	1,875W	2,500W	2,500W
Scalability	Max. 16 pcs in Parallel(20.48kWh)	Max. 16 pcs in Parallel(40.96kWh)	Max. 16 pcs in Parallel(60kWh)
Depth of Discharge(DOD)	≥95%		
Communication	RS485/CAN		
Protection Degree	IP21		
Cycle Life[2]	≥6,000 Cycles		
Charging Temperature Range	0°C~+55 °C		
Discharging Temperature Range	-20°C~+55 °C		
Display Type	LED		
Installation	Floor-Mounted		
Protection	Built-in smart BMS, Fuse		
Warranty Period	5 Years		
Certification	UN38.3		
Product Weight	10KG	15KG	26KG
Package Weight	12KG	18KG	29KG
Product Dimension	295X201X199MM	328X248X199MM	379X241X286MM
Package Dimension	357X263X261MM	391X310X257MM	443X305X344MM
[1] Max. Continuous Charge/Discharge Current is	Affected by Temperature and SOC.		
2] Test Conditions: 0.2C Charging/Discharging @	925°C,80% DOD		

 $<sup>{}^\</sup>star Product \, specifications \, may \, vary \, during \, continuous \, improvements. \, Please \, contact \, us \, for \, latest \, details.$ 

## **Product Display**



**Longer Lasting** LiFePO4 Battery



Support 16 Pcs in Parallel



Real-time Status via LCD Screen & LED



Wide Inverter Compatibility







 $<sup>{}^{\</sup>star}\mathsf{Refer}\ \mathsf{to}\ \mathsf{Felicitysolar's}\ \mathsf{Warranty}\ \mathsf{Policy}\ \mathsf{for}\ \mathsf{applicable}\ \mathsf{conditions}.$